

## SMC (Surmont Mix C)

### SECTION 1. IDENTIFICATION

<b>Product Identifier</b>	SMC (Surmont Mix C)
<b>SDS Number</b>	826066
<b>Other Means of Identification</b>	Petroleum Crude Oil
<b>Product Family</b>	Crude Oil
<b>Recommended Use</b>	Refinery feedstock.
<b>Restrictions on Use</b>	None known.
<b>Manufacturer/Supplier Identifier</b>	ConocoPhillips Canada Resources Corp. or its Affiliates P.O. Box 130, 401 - 9th Ave. SW Calgary, Alberta T2P 2H7
<b>Emergency Phone No.</b>	Chemtrec, 800-424-9300, (24 hr) CANUTEC, 1-800-CAN-UTEC (226-8832), (24 hr)

### SECTION 2. HAZARD IDENTIFICATION

#### Classification

Flammable liquid - Category 1; Acute toxicity (Oral) - Category 3; Acute toxicity (Dermal) - Category 4; Acute toxicity (Inhalation) - Category 3; Skin irritation - Category 2; Eye irritation - Category 2; Aspiration hazard - Category 1

#### Label Elements



Signal Word:  
Danger

#### Hazard Statement(s):

H225	Highly flammable liquid and vapour.
H301	Toxic if swallowed.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H320	Causes eye irritation.
H335	May cause respiratory irritation.
H401	Toxic to aquatic life.

#### Precautionary Statement(s):

P210	Keep away from heat, sparks, open flames, and hot surfaces. – No smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical, ventilating, lighting, and other equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P261	Avoid breathing vapours.
P280	Wear protective gloves/protective clothing.

Product Identifier:	SMC (Surmont Mix C)
Date of Preparation:	September 26, 2017
Date of Last Revision:	September 26, 2017

## SMC (Surmont Mix C)

**Other Hazards**
**EMERGENCY OVERVIEW :**

FLAMMABLE LIQUID AND VAPOUR. May form flammable/explosive vapour-air mixtures. Electrostatic charges may be generated during handling. Electrostatic discharges may cause fire.

CONTAINS HYDROGEN SULPHIDE. Product may contain hydrogen sulfide gas. H<sub>2</sub>S has a broad range of effects dependent on the airborne concentration and length of exposure: 0.02 ppm odour threshold, smell of rotten eggs; 10 ppm eye and respiratory tract irritation; 100 ppm coughing, headache, dizziness, nausea, eye irritation, loss of sense of smell in minutes; 200 ppm potential for pulmonary edema after >20-30 minutes; 500 ppm loss of consciousness after short exposures, potential for respiratory arrest; >1000 ppm immediate loss of consciousness, may lead rapidly to death, prompt cardiopulmonary resuscitation may be required. Do not depend on sense of smell for warning. H<sub>2</sub>S causes rapid olfactory fatigue (deadens sense of smell). There is no evidence that H<sub>2</sub>S will accumulate in the body tissue after repeated exposure.

**General Hygiene Comments :**

Do NOT eat, drink or store food in work areas.

Remove contaminated clothing and protective equipment before entering eating areas or leaving work area.

Wash hands thoroughly after handling this product and before eating, using the washroom or leaving work area.

### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No.	%	Other Identifiers
Crude Oil	8002-05-9	100	Not available
Methane	74-82-8	<0.01	Methyl hydride
Ethane	74-84-0	<0.01	Ethyl hydride
Propane	74-98-6	0.01 - 0.03	Propyl hydride
Isobutane	75-28-5	0.05 - 0.15	2-methylpropane
n-Butane	106-97-8	0.25 - 0.50	Butyl hydride
Isopentane	78-78-4	0.50 - 1.00	2-methylbutane
n-Pentane	109-66-0	0.75 - 1.25	Pentyl hydride
Hexanes	110-54-3	1.25 - 1.75	Not available
Heptanes	142-82-5	1.50 - 2.00	Not available
Octanes	111-65-9	1.75 - 2.25	Not available
Nonanes	111-84-2	1.50 - 2.00	Not available
Decanes+	124-18-5	90.00 - 92.00	Not available
Benzene	71-43-2	0.05 - 0.15	Benzol
Toluene	108-88-3	0.10 - 0.50	Methylbenzene
Ethylbenzene	100-41-4	0.05 - 0.15	Phenylethane
Xylene (mixed isomers)	1330-20-7	0.25 - 0.75	1,2/1,3/1,4-dimethylbenzene
Hydrogen Sulfide	7783-06-4	1 - 5 wppm	Sulfur hydride, acid gas

**Notes**

Concentrations are expressed in % weight/weight.

May contain trace amounts of hydrogen sulfide.

## SMC (Surmont Mix C)

### SECTION 4. FIRST-AID MEASURES

#### First-aid Measures

##### Inhalation

Take precautions to ensure your own safety before attempting rescue (e.g. wear appropriate protective equipment). Move to fresh air. Keep at rest in a position comfortable for breathing. If breathing is difficult, trained personnel should administer emergency oxygen if advised to do so by Poison Centre or doctor. If the victim has difficulty breathing or tightness in the chest, is dizzy, vomiting, or unresponsive, administer oxygen with rescue breathing or CPR as required. Obtain medical attention immediately.

##### Skin Contact

Avoid direct contact. Wear chemical protective clothing if necessary. Take off contaminated clothing, shoes and leather goods (e.g. watchbands, belts). Immediately wash gently and thoroughly with lukewarm, gently flowing water and mild soap for 15-20 minutes.

##### Eye Contact

Immediately rinse the contaminated eye(s) with lukewarm, gently flowing water for 15-20 minutes, while holding the eyelid(s) open. If eye irritation persists, get medical advice or attention.

##### Ingestion

Rinse mouth with water. Immediately call a Poison Centre or doctor. Do not induce vomiting.

#### Most Important Symptoms and Effects, Acute and Delayed

If inhaled:

Can irritate the nose and throat. Symptoms may include headache, nausea, dizziness, drowsiness and confusion.

If in eyes:

May cause moderate to severe irritation. Symptoms include sore, red eyes, and tearing.

If swallowed:

Small amounts can irritate the mouth, throat and stomach.

May be drawn into the lungs if swallowed or vomited, causing severe lung damage. Death can result.

#### Immediate Medical Attention and Special Treatment

##### Special Instructions

Treat symptomatically. Consult a Poison Control Centre for guidance.

### SECTION 5. FIRE-FIGHTING MEASURES

#### Extinguishing Media

##### Suitable Extinguishing Media

Small fire: Carbon dioxide, dry chemical powder, appropriate foam, water spray or fog.

Large fire: Water spray, fog or regular foam. Do not use straight streams.

Move containers from fire area if you can do it without risk.

Fire involving Tanks or Car/Trailer Loads:

Fight fire from maximum distance or use unmanned hose holders or monitor nozzles.

Cool containers with flooding quantities of water until well after fire is out.

Withdraw immediately in case of rising sound from venting safety devices or discoloration of tank.

ALWAYS stay away from tanks engulfed in fire.

For massive fire, use unmanned hose holders or monitor nozzles; if this is impossible, withdraw from area and let fire burn.

Product Identifier: SMC (Surmont Mix C)  
Date of Preparation: September 26, 2017  
Date of Last Revision: September 26, 2017

## SMC (Surmont Mix C)

### Unsuitable Extinguishing Media

Do not use water in a stream or jet.

### Specific Hazards Arising from the Product

May accumulate in hazardous amounts in low-lying areas especially inside confined spaces, resulting in a fire and/or health hazard.

### Special Protective Equipment and Precautions for Fire-fighters

Wear full protective clothing and self-contained breathing apparatus. Fight fire from a safe distance or a protected location. For a massive fire, immediately evacuate the area and use unmanned hose holder or monitor nozzles. Chemical protective clothing (e.g. chemical splash suit) and positive pressure SCBA may be necessary.

## SECTION 6. ACCIDENTAL RELEASE MEASURES

### Personal Precautions, Protective Equipment, and Emergency Procedures

Evacuate the area immediately. Isolate the hazard area. Keep out unnecessary and unprotected personnel. Evacuate downwind locations. Use the personal protective equipment recommended in Section 8 of this safety data sheet. Do not touch damaged containers or spilled product unless wearing appropriate protective equipment. Eliminate all ignition sources. Use grounded, explosion-proof equipment. Before entry, especially into confined areas, check atmosphere with an appropriate monitor.

### Environmental Precautions

Do not allow into any sewer, on the ground or into any waterway. If the spill is inside a building, prevent product from entering drains, ventilation systems and confined areas. Minimize the use of water to prevent environmental contamination.

### Methods and Materials for Containment and Cleaning Up

Small spills or leaks: stop or reduce leak if safe to do so. Contain and soak up spill with absorbent that does not react with spilled product. Do NOT use combustible materials such as sawdust. Place used absorbent into suitable, covered, labelled containers for disposal.

Large spills or leaks: dike spilled product to prevent runoff. Do not direct water at spill or source. Knock down vapour with fog or fine water spray.

### Other Information

Report spills to local health, safety and environmental authorities, as required.

## SECTION 7. HANDLING AND STORAGE

### Precautions for Safe Handling

Prevent uncontrolled release of product. Eliminate heat and ignition sources such as sparks, open flames, hot surfaces and static discharge. Post "No Smoking" signs. Do not use near welding operations or other high energy sources. Do not weld, cut or perform hot work on empty container until all traces of product have been removed. Electrically bond and ground equipment. Ground clips must contact bare metal. Do not carry or transfer this product in an enclosed space (e.g. in an elevator or inside a vehicle). Wear personal protective equipment to avoid direct contact with this chemical. Do not puncture or incinerate container even when empty.

## SMC (Surmont Mix C)

### Conditions for Safe Storage

Store in an area that is: cool, temperature-controlled, well-ventilated, separate from incompatible materials (see Section 10: Stability and Reactivity), clear of combustible and flammable materials (e.g. old rags, cardboard), out of direct sunlight and away from heat and ignition sources.

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters	ACGIH TLV®		OSHA PEL		AIHA WEEL	
	TWA	STEL	TWA	Ceiling	8-hr TWA	TWA
Methane	Not established					
Ethane	Not established					
Propane	1000 ppm					
Isobutane		1000 ppm				
n-Butane		1000 ppm	800 ppm			
Isopentane	600 ppm					
n-Pentane	600 ppm		1000 ppm			
Hexanes	50 ppm Skin		500 ppm			
Heptanes	400 ppm	500 ppm	500 ppm			
Octanes	300 ppm		500 ppm			
Nonanes	200 ppm					
Decanes+	Not established		Not established			
Benzene	0.5 ppm A1 Skin	2.5 ppm A1 Skin				
Toluene	20 ppm A4		200 ppm			
Ethylbenzene	100 ppm	125 ppm				
Xylene (mixed isomers)	100 ppm A4	150 ppm A4				
Hydrogen Sulfide	1 ppm	5 ppm		20 ppm		

### Appropriate Engineering Controls

Do not allow product to accumulate in the air in work or storage areas, or in confined spaces. Use local exhaust ventilation and enclosure, if necessary, to control amount in the air. If current ventilation practices are not adequate to maintain airborne concentrations below the established exposure limits, additional engineering controls may be required.

### Individual Protection Measures

#### Eye/Face Protection

Wear chemical safety goggles.

#### Skin Protection

Avoid repeated or prolonged skin contact. Wear chemical protective clothing e.g. gloves, aprons, boots.

#### Respiratory Protection

Not normally required if product is used as directed. Use appropriate OSHA/NIOSH approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

## SMC (Surmont Mix C)

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

#### Basic Physical and Chemical Properties

Appearance	Brown - black liquid.
Odour	Hydrocarbon, possibly faint rotten egg smell
Odour Threshold	Not available
pH	Not applicable
Melting Point/Freezing Point	Not available (melting); Not available (freezing)
Initial Boiling Point/Range	0 °C
Flash Point	< -20 °C (closed cup)
Evaporation Rate	Not available
Flammability (solid, gas)	Not applicable (liquid).
Upper/Lower Flammability or Explosive Limit	Not available (upper); Not available (lower)
Vapour Pressure	33.1 kPa at 37.8°C (100°F)
Vapour Density (air = 1)	> 1 (estimated)
Relative Density (water = 1)	0.942 - 0.944 at 15 °C
Solubility	Practically insoluble in water; Highly soluble in common organic solvents.
Partition Coefficient, n-Octanol/Water (Log Kow)	Not available
Auto-ignition Temperature	Not available
Decomposition Temperature	Not available
Viscosity	102.5 centistokes at 40 °C (104 °F) (kinematic)

#### Other Information

Physical State	Liquid
Molecular Formula	Not available
Molecular Weight	Not available

### SECTION 10. STABILITY AND REACTIVITY

#### Reactivity

Not reactive under normal conditions of use.

#### Chemical Stability

Normally stable.

#### Possibility of Hazardous Reactions

Not sensitive to mechanical impact.

#### Conditions to Avoid

Heat. High temperatures. Open flames, sparks, static discharge, heat and other ignition sources. Incompatible materials.

#### Incompatible Materials

Strong oxidizing agents (e.g. perchloric acid).

#### Hazardous Decomposition Products

Combustion releases carbon dioxide, trace amounts of sulfur oxides, and nitrogen oxides. A lack of oxygen during combustion can produce carbon monoxide and other toxic and flammable products. Hazardous decomposition products are not expected to form during normal storage.

## SMC (Surmont Mix C)

### SECTION 11. TOXICOLOGICAL INFORMATION

#### Likely Routes of Exposure

Inhalation; skin contact; eye contact; ingestion.

#### Acute Toxicity

Chemical Name	LC50	LD50 (oral)	LD50 (dermal)
Methane	Not available	Not available	Not applicable
Ethane	Not available	Not available	Not available
Propane	> 800000 ppm (rat) (30-minute exposure)	Not applicable	Not applicable
Isobutane	368000 mg/kg (male mouse) (4-hour exposure) (vapour)	> 5000 mg/kg	> 5000 mg/kg
n-Butane	658 mg/L (rat) (4-hour exposure)	Not available	Not available
Isopentane	140000 ppm (mouse) (2-hour exposure) (vapour)	> 2000 mg/kg (rat)	Not available
n-Pentane	6106 ppm (rat) (4-hour exposure)	> 2000 mg/kg (rat)	Not available
Hexanes	73680 ppm (rat) (4-hour exposure) (vapour)	32290 mg/kg (male rat)	> 3295 mg/kg (rabbit)
Heptanes	~ 25000 ppm (rat) (4-hour exposure)	> 15000 mg/kg (rat)	Not available
Octanes	25250 ppm (rat) (4-hour exposure)	Not available	Not available
Nonanes	3200 ppm (rat) (4-hour exposure)	> 15000 mg/kg	Not available
Decanes+	72300 mg/m <sup>3</sup> (mouse) (2-hour exposure) (aerosol)	Not available	Not available
Benzene	13700 ppm (rat) (4-hour exposure)	930 mg/kg (rat)	> 8240 mg/kg (rabbit)
Toluene	7585 ppm (rat) (4-hour exposure)	5580 mg/kg (male rat)	12125 mg/kg (rabbit)
Ethylbenzene	~ 4000 ppm (rat) (4-hour exposure)	3500 mg/kg (rat)	15380 mg/kg (rabbit)
Xylene (mixed isomers)	6350 ppm (male rat) (4-hour exposure)	3523 mg/kg (rat)	> 1700 mg/kg (rabbit)
Hydrogen Sulfide	444 ppm (rat) (4-hour exposure)	Not available	Not available

#### Skin Corrosion/Irritation

May cause mild irritation based on information for closely related chemicals. Contact may cause irritation to the skin and mucous membranes upon prolonged and/or repeated skin contact. Prolonged or repeated contact to petroleum oil with skin may cause defatting of the skin leading to redness, itching, inflammation, cracking, dermatitis (rash).

#### Serious Eye Damage/Irritation

May be irritating to eyes. Symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

## SMC (Surmont Mix C)

### STOT (Specific Target Organ Toxicity) - Single Exposure

#### Inhalation

Not an expected route of exposure, but vapours may cause irritation of the nose and throat. CONTAINS HYDROGEN SULPHIDE! : Short term exposure effects may include depression of the central nervous system, resulting in dizziness, light-headedness, headache, nausea, or unconsciousness. Death by asphyxiation or from the toxic effects of hydrogen sulphide is a danger from prolonged exposure.

#### Skin Absorption

Liquid may be absorbed through the skin if large areas of skin are exposed.

#### Ingestion

May cause gastrointestinal irritation. Symptoms may include abdominal pain, stomach upset, nausea, vomiting, and diarrhea.

If small amounts are ingested: can irritate the mouth, throat and stomach.

If large amounts are ingested: harmful.

### Aspiration Hazard

May be drawn into the lungs (aspirated) if swallowed or vomited.

### STOT (Specific Target Organ Toxicity) - Repeated Exposure

Material in general is not expected to cause harm.

### Respiratory and/or Skin Sensitization

Not a respiratory sensitizer. Not a skin sensitizer.

### Carcinogenicity

Chemical Name	IARC	ACGIH®	NTP	OSHA
Benzene	Group 1	A1	Known carcinogen	Carcinogen

The material in general is not considered a carcinogen, however, all appropriate precautions should still be taken due to the presence of benzene in the product.

### Reproductive Toxicity

#### Development of Offspring

Material in general is not expected to cause harm. The material in general is not expected to produce teratogenic or embryotoxic effects.

#### Sexual Function and Fertility

Material in general is not expected to cause harm. The material in general is not expected to have toxic reproductive effects.

#### Effects on or via Lactation

No information was located.

### Germ Cell Mutagenicity

Material in general is not expected to cause harm. The material in general is not expected to produce mutagenic effects

### Interactive Effects

No information was located.



## SMC (Surmont Mix C)

### SECTION 12. ECOLOGICAL INFORMATION

**Ecotoxicity**

Harmful to aquatic life, animals, birds.

**Persistence and Degradability**

Not expected to be removed rapidly from aquatic environments by evaporation.

**Bioaccumulative Potential**

This product and its degradation products are not expected to bioaccumulate.

**Mobility in Soil**

If released into the environment, this product is expected to move slowly through the soil, based on physical and chemical properties. Contamination of groundwater could occur. If released into soil, this material will absorb and may biodegrade in anaerobic conditions. In water it may become volatile. Photo-oxidation products may include phenol, nitrophenols, nitrobenzene, formic acid.

**Other Adverse Effects**

There is no information available.

### SECTION 13. DISPOSAL CONSIDERATIONS

**Disposal Methods**

Material Disposal:

This product and its container must be disposed of as hazardous waste. Do NOT dump into any sewers, on the ground or into any body of water. Do not discharge into areas where there is a risk of forming an explosive mixture with air.

Local Legislation:

Disposal should be in accordance with applicable regional, national, and local laws and regulations. Local regulations may be more stringent than regional or national requirements and must be complied with.

### SECTION 14. TRANSPORT INFORMATION

Regulation	UN No.	Proper Shipping Name	Transport Hazard Class(es)	Packing Group Group
Canadian TDG	1267	PETROLEUM CRUDE OIL	3	I
US DOT	1267	PETROLEUM CRUDE OIL	3	I

**Environmental Hazards** Potential Marine Pollutant

**Special Precaution** Please note: CONTAINS HYDROGEN SULFIDE : May evolve hazardous levels of H2S in headspace volumes of closed tanks and vessels.

**Transport in Bulk According to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable

**Emergency Response Guide No.** GUIDE 128

## SMC (Surmont Mix C)

### SECTION 15. REGULATORY INFORMATION

#### Safety, Health and Environmental Regulations

This section is not required by WHMIS 2015.

### SECTION 16. OTHER INFORMATION

**NFPA Rating**      **Health - 3**                      **Flammability - 3**    **Instability - 0**

**SDS Prepared By**                      Maxxam Analytics  
**Phone No.**                                1-800-386-7247

**Date of Preparation**                    September 26, 2017  
**Date of Last Revision**                September 26, 2017

**Revision Indicators**                 Not applicable

**Key to Abbreviations**                ACGIH® = American Conference of Governmental Industrial Hygienists  
    OSHA = US Occupational Safety and Health Administration  
    RTECS® = Registry of Toxic Effects of Chemical Substances

**References**                                CHEMINFO database. Canadian Centre for Occupational Health and Safety (CCOHS).  
    Registry of Toxic Effects of Chemical Substances (RTECS®) database. Dassault  
    Systèmes/BIOVIA ("BIOVIA"). Available from Canadian Centre for Occupational Health and  
    Safety (CCOHS).

**Disclaimer**                                This SDS provides safety information and was developed for employees, customers and  
    agents of ConocoPhillips from data obtained from the sample(s) submitted for analysis. The  
    information may not be valid or complete if the product or material is used in combination with  
    other products or materials, or in any process. This information is intended for reasonable  
    normal usage and recommended practices, and to underscore the potential hazards that may  
    be inherent to the nature of the product or material. Although every effort is made to ensure  
    accuracy and completeness of the contained information, it is understood that Maxxam  
    Analytics makes no warranty as to the accuracy or completeness of information and assumes  
    no liability for any damage or loss suffered as result of any inaccuracy or incompleteness  
    therein. This information is considered to be as accurate as possible, as of the date of  
    preparation. The reader is invited to contact ConocoPhillips at the address shown to ensure  
    the information is up to date or to obtain further information related to an unusual or other use.

SDS representative sample(s) :

ConocoPhillips Crude Blend B1